



**SERIES ROTOR
ROTOSWITCH**
CODE 410249



Datasheet

Electrical characteristics

Rated current	32A
Supply Voltage	230V 50/60Hz ●
Poles	3P+N+ \perp
Clock Position	9h
Rated insulation voltage	690V
Insulation Class	II
Protection	-
Signal plug inserted	-

Mechanical characteristics

Manufacturing material	High resistance technopolymer
Treatment type	-
Surface finishing	-
Color	Blue RAL 5015, Grey RAL 7046
Width	-
Execution	Mobile
Hole type	Cable clamp (13 to 27mm cables)
Protection degree	IP66/IP67
Additional degree protection	IP69 - IEC 60529
Shock resistance	IK10 according to IEC/EN 62262
Resistance to Glow wire	850°C (Casing), 960°C (Live contacts)
Flame rating according UL94	V-0 (Live contacts), V-2 (Casing)
Corrosivity category	-
Net Weight	0.85 KG
Working Environment Temp.	Min: -40°C ;Max: +60°C
Warehousing Temperature	Min: -50°C ;Max: +90°C

Technical data switch

Thermal current	32 A
Rated short-circuit current	10 kA
Terminals type	Screw - indirect clamping
Conductors section	Min: 1 mm ² ;Max: 10 mm ²
Terminal tightening torque	2 Nm
Auxiliary status contacts	-
Padlockable handle	2 locks Ø2,75 mm max

Operating category

Categoria Rating	Tensione Voltage	Corrente / Potenza Current / Power
AC-22A	230 V	32 A
	400 V	32 A
	500 V	32 A
	690 V	32 A
AC-23A	230 V	32 A
	400 V	32 A
	500 V	32 A
	690 V	32 A
AC-23A	230 V	10.2 Kw
	400 V	17.7 kW
	500 V	22.2 kW
	690 V	30.6 kW

Reference Standards and Directives

Certification and approval marks UKCA, NYCE COLOMBIA, CE

Directives 2012/19/EU (WEEE), 2014/35/EU (LVD), 2011/65/EU (RoHS)

Reference Standards EN 60309-2:1999, EN 60309-1:1999, EN 63000:2018, EN 60309-1:1999/A2:2012, EN 60309-1:1999/A1:2007, EN 60309-4:2007, EN 60309-1:1999/A1AC:2014, EN 60309 2:1999/A2:2012, EN 60309-4:2007/A1:2012, EN 60309-2:1999/A1:2007

The images are purely indicative. Palazzoli reserves the right to make changes without notice.