



**SERIES X-CEE
PLUG
CODE 769126**



Datasheet

Electrical characteristics

| | |
|--------------------------|----------------|
| Rated current | 16A |
| Supply Voltage | 230V 50/60Hz ● |
| Poles | 2P+ \perp |
| Clock Position | 6h |
| Rated insulation voltage | 690V |
| Signal plug inserted | - |

Reference Standards and Directives

| | |
|----------------------------------|---|
| Certification and approval marks | NYCE COLOMBIA, UKCA, CE |
| Directives | 2011/65/EU (RoHS), 2014/35/EU (LVD), 2012/19/EU (WEEE) |
| Reference Standards | EN 60309-1:1999/A1AC:2014, EN 50581:2012, EN 60309-2:1999/A1:2007, EN 63000:2018, EN 60309-1:1999, EN 60309 1:1999/A1:2007, EN 60309-1:1999/A2:2012, EN 60309-2:1999/A2:2012, EN 60309-2:1999 |

Mechanical characteristics

| | |
|------------------------------|---|
| Manufacturing material | High resistance technopolymer |
| Alveolus/plugs treatment | Nickel plated |
| Color | Grey RAL 7046, Blue RAL 5015 |
| Tightening diameter | - |
| Execution | - |
| Protection degree | IP66/IP67 |
| Additional degree protection | IP68/IP69 - IEC 60529 |
| Shock resistance | IK10 according to IEC/EN 62262 |
| Resistance to Glow wire | 960°C (Live contacts), 850°C (Casing) |
| Flame rating according UL94 | V-2 (Casing), V-0 (Live contacts) |
| Terminals type | Screw - indirect clamping |
| Conductors section | Min: 1 mm ² ;Max: 10 mm ² |
| Terminal tightening torque | 2 Nm |
| Net Weight | 0.117 KG |
| Working Environment Temp. | Min: -40°C ;Max: +60°C |
| Warehousing Temperature | Min: -50°C ;Max: +90°C |

The images are purely indicative. Palazzoli reserves the right to make changes without notice.